

HOSES LAYFLAT

SUNNYHOSE® Heavy Duty Red Layflat Hose

APPLICATION: Well suited for water drainage at open pit mining and at civil engineering/dam construction sites in mountains or other areas where water must be moved to significantly higher or lower elevations.

REINFORCEMENT: High strength yarn.

INNER TUBE: PVC compound.

COVER: PVC compound.

TEMPERATURE: -10°C to +60°C

ADVANTAGES:

- Abrasion resistant.



Pre-made Hose Assemblies

Part Number	Hose Size / mm		Working Pressure	Weight	Lengths
	ID	OD	Max	kg/m	metres
04-010-038-***	40	1.9	152	0.29	100
04-010-051-***	52.5	2.05	152	0.42	100
04-010-063-***	66	2.15	152	0.54	100
04-010-076-***	78.5	2.25	130	0.66	100
04-010-102-***	104	2.55	130	1.00	100
04-010-152-***	155	2.95	102	1.68	100
04-010-203-***	207	2.95	75	2.20	100

QUEENSLAND

Brisbane (07) 3722 3722
Geebung (07) 3722 3722
Mackay (07) 4847 7000
Townsville (07) 4412 8420

NEW SOUTH WALES

Sydney
- Wetherill Park (02) 8786 7200
- Newcastle (02) 4918 5400

VICTORIA

Melbourne
- Dandenong (03) 8544 5800
- Deer Park (03) 7379 8200
- Bayswater (03) 9753 8400

WESTERN AUSTRALIA

Perth (08) 9251 2900

TASMANIA

Hobart (03) 6242 4700